

PUBLIC ADDRESS / SPEAKERS / SOUND PROJECTORS

PF-21T

BIDIRECTIONAL SOUND PROJECTOR





Excellent sound quality Large coverage angle IP-44 protection

ESPECIALLY RECOMMENDED IN:







Education



Transport Stations



All sectors



DESCRIPTION

High impedance sound projectorSound projector with great features, design and manufacture. Bidirectional sound emission. Its features make it very suitable for indoor or outdoor PA installations, IP-44 protection. It is built in ABS with hermetic casing, which guarantees its resistance and performance in aggressive environments. It offers a clear and clean sound, perfect for PA and background music applications. With 150° dispersion and a sensitivity of 94 dB at 1 W/1 m, it can reach great distances and cover large areas. Includes stainless steel mounting bracket for easy installation, minimising installation time. For PA and background music in 100 V line installations in shopping centres, schools, hospitals, sports facilities, industrial warehouses, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Bidirectional sound projector with 100, 70 and 50 V line transformer.
POWER	30 W max, 20 W RMS
LOUDSPEAKERS	2 x 6 ½'
RESPONSE	100-20,000 Hz
IMPEDANCE	20 W RMS@100 V (500 Ohm) 10 W RMS@100 V (1.000 Ohm) 5 W RMS@100 V (2.000 Ohm)
SENSITIVITY	94 dB at 1 W/1 m
DISPERSION	150° bidirectional
PROTECTION	IP-44
MATERIAL	ABS. Hermetic casing. Stainless steel mount.
COLOUR	Ivory (RAL 9001)
DIMENSIONS	180 mm Ø x 251 mm depth
WEIGHT	2.9 kg
ACCESSORIES	Adjustable fixing mount