

HIGH POWER / SPEAKERS / LIABILITIES

FORCE-8

PASSIVE HIGH-POWER LOUDSPEAKER.











High power with rich sound



Robust structure and high quality components



Carrying handles, suspension points and hole in base for 35 mm tube



User-friendly and intuitive



ESPECIALLY RECOMMENDED IN:







Hotels



Sports facilities

ies Hospitality

All sectors

DESCRIPTION

High power loudspeakerFONESTAR has developed the FORCE high power loudspeaker range. Speakers that deliver a powerful sound with great detail, specially designed for portable or fixed sound systems. They feature a heavy-duty injection case with handles for easy and safe transport and high-quality components. Excellent grain paint finish. Suspension points and hole in base for 35 mm tube for suspension or stand installation. Front metal grille ensures speaker integrity.Perfect for disco-mobile applications, discos, pubs, gyms, restaurants, events or parties, etc.

TECHNICAL CHARACTERISTICS

Hole in the base for 35 mm tube. 600 W peak, 200 W RMS 1 x 8" woofer: 50 mm coil and 134 mm ferrite magnet 1 x 1" compression driver: 25 mm coil and 80 mm magnet 65-18,000 Hz IMPEDANCE 8 Ohm SENSITIVITY 95 dB at 1 W/1 m SOUND PRESSURE 120 dB at maximum power at 1 m DISPERSION 90° H x 90° V CONNECTORS (1+, 1-) Passive, 2 way Crossover frequency 2,500 Hz, -9 dB/octave 4 M8 points COLOUR Black DIMENSIONS 290 x 470 x 260 mm depth WEIGHT 10.7 kg	FEATURES	High power speaker. Injection-moulded case. Textured paint finish. Carrying straps. Suspension points.
1 x 8" woofer: 50 mm coil and 134 mm ferrite magnet 1 x 1" compression driver: 25 mm coil and 80 mm magnet 65-18,000 Hz 1MPEDANCE 8 Ohm 95 dB at 1 W/1 m SOUND PRESSURE 120 dB at maximum power at 1 m DISPERSION 90° H x 90° V CONNECTORS (1+, 1-) Passive, 2 way Crossover frequency 2,500 Hz, -9 dB/octave SUSPENSION POINTS 4 M8 points COLOUR Black DIMENSIONS 290 x 470 x 260 mm depth	POWFR	
IMPEDANCE SENSITIVITY 95 dB at 1 W/1 m 120 dB at maximum power at 1 m DISPERSION 90° H x 90° V 2 x 4-contact loudspeaker connectors (1+, 1-) Passive, 2 way Crossover frequency 2,500 Hz, -9 dB/octave SUSPENSION POINTS 4 M8 points COLOUR Black DIMENSIONS 290 x 470 x 260 mm depth		1 x 8" woofer: 50 mm coil and 134 mm ferrite magnet
SENSITIVITY 95 dB at 1 W/1 m 120 dB at maximum power at 1 m DISPERSION 90° H x 90° V 2 x 4-contact loudspeaker connectors (1+, 1-) Passive, 2 way Crossover frequency 2,500 Hz, -9 dB/octave SUSPENSION POINTS 4 M8 points COLOUR Black DIMENSIONS 290 x 470 x 260 mm depth	RESPONSE	65-18,000 Hz
SOUND PRESSURE DISPERSION 90° H x 90° V CONNECTORS (1+,1-) Passive, 2 way Crossover frequency 2,500 Hz, -9 dB/octave SUSPENSION POINTS A M8 points COLOUR Black DIMENSIONS 120 dB at maximum power at 1 m 90° H x 90° V 2 x 4-contact loudspeaker connectors (1+, 1-) Passive, 2 way Crossover frequency 2,500 Hz, -9 dB/octave	IMPEDANCE	8 Ohm
DISPERSION 90° H x 90° V 2 x 4-contact loudspeaker connectors (1+, 1-) CROSSOVER CROSSOVER Passive, 2 way Crossover frequency 2,500 Hz, -9 dB/octave 4 M8 points COLOUR Black DIMENSIONS 290 x 470 x 260 mm depth	SENSITIVITY	95 dB at 1 W/1 m
CONNECTORS 2 x 4-contact loudspeaker connectors (1+,1-) Passive, 2 way Crossover frequency 2,500 Hz, -9 dB/octave 4 M8 points COLOUR Black DIMENSIONS 2 x 4-contact loudspeaker connectors (1+,1-) Passive, 2 way Crossover frequency 2,500 Hz, -9 dB/octave 4 M8 points 2 x 4-contact loudspeaker connectors (1+,1-)	SOUND PRESSURE	120 dB at maximum power at 1 m
CROSSOVER CROSSOVER CROSSOVER Crossover frequency 2,500 Hz, -9 dB/octave 4 M8 points COLOUR Black DIMENSIONS 290 x 470 x 260 mm depth	DISPERSION	90° H x 90° V
Crossover frequency 2,500 Hz, -9 dB/octave SUSPENSION POINTS 4 M8 points COLOUR Black DIMENSIONS 290 x 470 x 260 mm depth	CONNECTORS	
COLOUR Black DIMENSIONS 290 x 470 x 260 mm depth	CROSSOVER	•
DIMENSIONS 290 x 470 x 260 mm depth	SUSPENSION POINTS	4 M8 points
	COLOUR	Black
WEIGHT 10.7 kg	DIMENSIONS	290 x 470 x 260 mm depth
	WEIGHT	10.7 kg







