

MICROPHONES / CONFERENCE SYSTEMS / DIGITAL

SCD-620D

DELEGATE MICROPHONE FOR DIGITAL CONFERENCE SYSTEM



- ✓ Crystal clear voice pick-up
- ✓ Information display
- ✓ Voting buttons.
- ✓ Monitor speaker and gooseneck microphone

ESPECIALLY RECOMMENDED IN:



Education



Offices

DESCRIPTION

Delegate microphoneDelegate microphone for conference system mod. SCD-600. LCD information display, voting buttons, monitor loudspeaker and headphone output, in addition, they do not require any additional power supply and are immediately recognised by the SCD-600 central unit without configuration.Cat 5e, Cat 6 cable connection.Conference rooms, plenary sessions, parliaments, business centres, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Delegate microphone. Information display. Voting buttons. Built-in monitor speaker. Gooseneck microphone. Data and audio transmission. Cat 5e, Cat 6 cable connection (see note).
MICROPHONE	Unidirectional electret condenser with LED ring
DIMENSIONS	Gooseneck microphone: 440 mm Base: 170 x 39 x 172 mm depth
WEIGHT	0.7 kg
ACCESSORIES	Windshielded foam Cat 5e / FTP network cable with shielded connectors, 2 m length
NOTE	It is necessary to use high quality Cat 5e/6 cables with FTP/SFTP shielding, 24 AWG. Cables should have shielded connectors with the cable shielding connected to the connector shield. Maximum cable length 100 m. Cables between microphones should not exceed 2-3 metres.