

SYSTEMS AND CONTROL / ZONE SYSTEMS / DIGITAL

# MPX-430VS

VOLUME CONTROL AND ZONE SELECTION 2 OUTPUTS REMOTE CONTROL



- ✓ Allows for volume control and zone selection
- ✓ 2 x audio output channels
- ✓ LCD display

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

Volume control with two balanced audio outputs and zone allocation for audio matrix mod. MPX-4088.Connection to the matrix via RJ-45, Cat 5e cable.

TECHNICAL CHARACTERISTICS

FEATURES	Volume control with two balanced audio outputs and zone allocation for audio matrix mod. MPX-4088. Connection to RD ports. Connection to the matrix via RJ-45, Cat 5e cable. LCD display with volume level information for the selected output.
INPUTS	1 RD port for connection to matrix MPX-4088, RJ-45
OUTPUTS	2 balanced line, euroblock, 240 Ohm, 7.74 V, assignable to digital channels 9/10 or 11/12.
CONTROLS	Volume control and zone allocation
CONNECTION	RJ-45, Cat 5e cable
POWER SUPPLY	24 V DC, 100 mA, RD port
DIMENSIONS	147 x 86 x 47 mm depth
WEIGHT	0.23 kg
ACCESSORIES	Surface box